

Elite Dryfall -Technical Data & Specification Sheet

Contact Pristine Coatings on 01492 544777

Product Name: Elite Dryfall.

Supplier: Pristine Coatings, Unit 10 Phoenix Workshops, Station Rd, Mochdre, Colwyn Bay, LL28 5EF. Tel 01492 544777

Description: Elite Dryfall is specially formulated for spray application to interiors in commercial and institutional premises, especially interior cladding. The overspray will turn to dust before hitting the floor. This Feature reduces time spent on costly clean up and masking.

Where to Use: Interior cladding, galvanised steel, Metal-Pan ceiling tiles, drywall, plaster, metal & concrete, walls and primed structural steel.

Properties:

- Ideal for interior applications
- Waterbased
- Washable sheen finish for metal tiles & cladding
- Excellent productivity
- Self priming
- Excellent adhesion
- Fully permeable
- Minimum masking
- High light reflectance

Specification

Preparation: Remove any contamination that would be detrimental to adhesion. sand down any glossy surfaces to form a key. Prime any rust or bare patches on structural steel. Brush down surface to remove dust & cobwebs, degrease if required. Mask & protect the area if necessary

Application:

Do not dilute, product is ready for application by airless spray. apply Elite Dryfall onto substrate . use Airless Spray with tip size .013 to .015 with 12 inch fan apply Elite Dryfall overlapping each pass of sprayer by 50% to ensure uniform coverage.

Completion: On completion of spraying leave overspray at least 20 minutes to settle before de-masking. Clean machine and equipment with warm water, ensure the areas are clean & ready for re-occupation.

Tech data:

Colour	White as standard but can be supplied in any RAL or BS colour
Solids	39%
Spread rate	10m ² per litre depending on substrate.
Dry to touch	45 minutes
Recoat after	4 hours
Clean-up	Warm Soapy Water
Flash Point	100°C
WFT	between 150 & 200 microns
Containers	20 litres
Weight	21 Kilos

